



Artikelnummer	2700210620
Fabriekaart	Schneider Electric
Typenummer	A9A26929
Artikelnummer Leverancier	A9A26929
EAN Code	3606480087882

Minimale afname 1

Product omschrijving

This Acti9 iOF+SD/OF electric auxiliary is a double open/closed or fault indicator contact. It is dedicated to iC60, iC40, iCV40, iLD, iLD40, iDPN Vigi, iSW-NA, iC60 & iLD products. It comes with 1 changeover contact indicating the open or closed position (OF). It provides a remote position open/close and/or fault tripping indication of the associated device. It is a two-in-one product. The choice of OF+SD or OF+OF contact is made via the selector switch on front face. There is a mechanical state indicator and a test function button on the front face. The Ue rated operational voltage is 24VAC to 415VAC or 24VDC to 130VDC. The operating frequency is 50Hz or 60Hz. The Ie rated operational current is 6A under 24VDC, 2A under 48VDC, 1.5A under 60VDC, 1A under 130VDC. The Ie rated operational current is 6A under 24VAC to 240VAC, 3A under 415VAC. The width in 9mm pitches is 1. The product color is white (RAL9003). The dimensions are (W) 9mm x (H) 86mm x (D) 73mm. Product weight is 32g. The degree of protection is IP20 at terminals and IP40 in enclosure. The operating temperature is -35°C to +70°C. The storage temperature is -40°C to +85°C. This product complies with EN/IEC 60947-5-1 standard.

Technische specificaties

Apparaatmontage	Aardlekautomaat en installatieautomaat
Nevenapparaat	Hulpschakelaar/foutsignalschakelaar
In de fabriek aangebracht	Nee
Bouwbreedte (TE)	0.5
Aantal contacten als wisselcontact	2
Aantal foutsignalschakelaars	1
Nom. (meet)schakelstroom	1 A
Nom. (meet)spanning	240 V
Type stuurspanning	AC

Met autotest voor aardlekfunctie Nee

Geschikt voor max. aantal polen hoofdapparaat (totaal) 4

Geschikt voor max. stroom hoofdapparaat 63 A