



Artikelnummer	2700211791
Fabrikaat	Schneider Electric
Typenummer	A9N26924
Artikelnummer Leverancier	A9N26924
EAN Code	3606480382925

Minimale afname 1

### Product omschrijving

This Acti9 OF+SD/OF electric auxiliary is a double open/closed or fault indicator contact. It is dedicated to C60, C40, C120, C40, iID, DT40, iDPN Vigi, SW60-DC, iTG40 products. It comes with 1 changeover contact indicating the open or closed position (OF). It provides a remote position open/close and/or fault tripping indication of the associated device. It is a two-in-one product. The choice of OF+SD or OF+OF contact is made via the selector switch on front face. There is a mechanical state indicator and a test function button on the front face. The Ue rated operational voltage is 24VAC to 415VAC or 24VDC to 130VDC. The operating frequency is 50Hz or 60Hz. The Ie rated operational current is 6A under 24VDC, 2A under 48VDC, 1.5A under 60VDC, 1A under 130VDC. The Ie rated operational current is 6A under 24VAC to 240VAC, 3A under 415VAC. The width in 9mm pitches is 1. The product color is white (RAL9003). The dimensions are (W) 9mm x (H) 85.3mm x (D) 73.5mm. Product weight is 30g. The degree of protection is IP20 at terminals and IP40 in enclosure. The operating temperature is -25°C to +50°C. The storage temperature is -40°C to +85°C. This product complies with EN/IEC 60947-5-1 standard.

### Technische specificaties

Apparaatmontage	Installatieautomaat
Nevenapparaat	Signaalschakelaar
In de fabriek aangebracht	Nee
Bouwbreedte (TE)	0.5
Aantal contacten als wisselcontact	1
Aantal foutsignaalschakelaars	1
Nom. (meet)schakelstroom	6 A
Nom. (meet)spanning	240 V
Type stuurspanning	AC

Met autotest voor aardlekfunctie Nee

Geschikt voor max. aantal polen hoofdapparaat (totaal) 4

Geschikt voor max. stroom hoofdapparaat 125 A